



Artikel Nr. Item no.	Beschreibung Description
50910	AK 0050 0.5m
11510	AK 0150 1.5m
11511	AK 0250 2.5m
11512	AK 0500 5.0m
11513	AK 0750 7.5m
11514	AK 1000 10.0m
11515	AK 1500 15.0m
50125	AK 2000 20.0m



Antennenkabel (<70 dB), doppelt geschirmt

- Doppelt geschirmtes Satellitenkabel für eine störungsfreie Übertragung
- Beidseitig vergossener Stecker zum Schutz vor Staub, Schmutz und mechanischen Belastungen
- Koaxialkabel mit vernickelten, passgenauen Kontakte
- Fernseekabel zum Anschluss von Geräten mit Koaxial-Anschluss wie z. B. Fernseher, Receiver und Radios

Anschlüsse:	Koax-Buchse, Koax-Stecker
Kabeltyp:	Koaxialkabel
Material Kabelmantel:	PVC
Kabelmantel:	Ø 5 mm
Material Innenleiter:	CCS
Innenleiter:	Ø 0.5 mm
Anzahl Schirmungen:	2 x
Material Schirmungen:	Folie (Alu), Geflecht (Alu) 32x
Schirmungsmaß:	70 dB
Wellenwiderstand:	75 Ω

Antenna Cable (<70 dB), Double Shielded

- Double shielded satellite cable for interference-free transmission
- Molded plug on both sides to protect against dust, dirt and mechanical stresses
- Coaxial cable with nickel-plated, precision-fit contacts
- TV aerial cable for connecting devices with a coaxial connection such as televisions, receivers and radios

Connections:	coaxial female, coaxial male
Cable type:	coaxial cable
Material cable jacket:	PVC
Cable sheath:	Ø 5 mm
Material inner conductor:	CCS
Inner conductor:	Ø 0.5 mm
Number of shieldings:	2 x
Material shielding:	foil (aluminium); braid (aluminium) 32x
Shielding efficiency:	70 dB
Impedance:	75 Ω

Änderungen			Datum	Name	Bezeichnung	 by Wentronic GmbH Pillmannstraße 12 38112 Braunschweig Germany	Blatt
Datum	Name	gez.:	17.02.2026	ir	AK XXXX X.Xm		1/1
		gepr.:	17.02.2026	ir			
		Norm:			Zeichnungs-Nr.:		von
		Änderungen vorbehalten / Subject to change			11510ff		